ELECTRA CABLES (Aust.) Pty. Limited

Low Smoke Zero Halogen - Flat TPS Cables
LSZH 450/750V 2& 3 core + Earth flat.

Application: For light to medium industrial use. For festoon systems and other applications. Suitable for all building internal wiring applications.

Conductor: Plain annealed copper (AS/NZS 1125)
Insulation: X-HF-90 90°C LSZH
Sheath: X-HF-90 90°C LSZH
Standard: AS/NZS 5000.2
Packing Length: 100m, 500m
Normal Operating Temperature: 90°C



Typical Features:

Electra Cables Part No.	Stranding No./mm	Conductor area mm	Insulation Thickness mm	Sheath Thickness mm	Nom. O/D mm	Approx. Mass kg/100 m
2 Core Twin or Twin Active (No Earth)						
SRF2015VLS	7/0.50	1.5	0.6	0.9	7.2×4.6	6.2
SRF2025VLS	7/0.67	2.5	0.7	1.0	8.9×5.5	9.7
SRF2040VLS	7/0.85	4.0	0.8	1.1	10.6×6.5	14.3
SRF2060VLS	7/1.04	6.0	0.8	1.1	11.7×7.1	18.5
2 Core + Earth						
SRF3015VLS	7/0.50	1.5	0.6	0.9	10.0×4.6	8.85
SRF3025VLS	7/0.67	2.5	0.7	1.0	12.4×5.5	13.7
SRF3040VLS	7/0.85	4.0	0.8	1.1	14.0×6.5	18.7
SRF3060VLS	7/1.04	6.0	0.8	1.1	15.2×7.1	23
3 Core + Earth						
SRF4015VLS	7/0.50	1.5	0.6	0.9	12.6×4.6	11.5
SRF4025VLS	7/0.67	2.5	0.7	1.0	15.8×5.5	18.3