SG50CX Premium

Multi-MPPT String Inverter for 1000 Vdc System

AU



HIGH YIELD

- Up to 5 MPPTs with max. efficiency 98.7%
- Compatible with bifacial module
- Built-in PID recovery function

SMART O&M

- Touch free commissioning and remote firmware upgrade
- Smart IV curve scanning *
- Fuse free design with smart string current monitoring

SAVED INVESTMENT

- Compatible with Al and Cu AC cables
- DC 2 in 1 connection enabled
- Cable free communication with optional WLAN

PROVEN SAFETY

- IP66 and C5 anti-corrosion
- Type II SPD for DC and AC

CIRCUIT DIAGRAM



EFFICIENCY CURVE



© 2021 Sungrow Power Supply Co., Ltd. All rights reserved. Subject to change without notice. Version 1.1

SUNGROW
Clean power for all

Type designation	SG50CX
Input (DC)	
Max. PV input voltage	1100 V **
Min. PV input voltage / Start-up input voltage	200 V / 250 V
Nominal PV input voltage	585 V
MPP voltage range	200 – 1000 V
No. of independent MPP inputs	5
No. of PV strings per MPPT	2
Max. PV input current	130 A
Max. DC short-circuit current	200 A
Output (AC)	
AC output power	50 kVA
Max. AC output current	80.5 A
Nominal AC voltage	3 / N / PE, 230 / 400 V
AC voltage range	312 – 528 V
Nominal grid frequency / Grid frequency range	50 Hz / 45 – 55 Hz, 60 Hz / 55 – 65 Hz
Harmonic (THD)	< 3 % (at nominal power)
Power factor at nominal power / Adjustable power factor	> 0.99 / 0.8 leading – 0.8 lagging
Feed-in phases / AC connection	3 / 3-PE
Efficiency	
Max. efficiency / European efficiency	98.7 % / 98.4 %
Protection and function	
DC reverse polarity protection	Yes
AC short-circuit protection	Yes
Leakage current protection	Yes
Grid monitoring	Yes
Ground fault monitoring	Yes
DC switch	Yes
AC switch	No
PV string monitoring	Yes
Q at night function	Yes
PID recovery function	Yes
DC terminal protective cover	Yes
Surge protection	DC Type II / AC Type II
General Data	
Dimensions (W * H * D)	782 * 645 * 310 mm
Weight	62 kg
Topology	Transformerless
Degree of protection	IP66
Night power consumption	≤2 W
Operating ambient temperature range	-30 to 60 ℃ (> 45 ℃ derating)
Allowable relative humidity range	0 – 100 %
Cooling method	Smart forced air cooling
Max. operating altitude	4000 m (> 3000 m derating)
Display	LED, Bluetooth+APP
Communication	RS485 / WLAN / Optional: Ethernet
DC connection type	MC4 (Max. 6 mm²)
AC connection type	OT or DT terminal (Max.70 mm²)
Compliance	IEC 62109, IEC 61727, IEC 62116, IEC 60068, IEC 61683, IEC 61000-6-3, AS/NZS 4777.2:2015
Grid Support	Q at night function, LVRT, HVRT,active & reactive power control and power ramp rate control

* Only compatible with Sungrow Logger, EyeM4 and iSolarCloud
** Max. operating DC voltage is 1000V, max. withstanding DC voltage is 1100 V

© 2021 Sungrow Power Supply Co., Ltd. All rights reserved. Subject to change without notice. Version 1.1